



U.S. ENVIRONMENTAL PROTECTION AGENCY
 Office of Pesticide Programs
 Antimicrobials Division (7510P)
 1200 Pennsylvania Ave., N.W.
 Washington, D.C. 20460

EPA Reg. Number:

39967-130

Date of Issuance:

10/5/15

NOTICE OF PESTICIDE:

Registration
 Reregistration
 (under FIFRA, as amended)

Term of Issuance:

Conditional

Name of Pesticide Product:

PREVENTOL P 30 S

Name and Address of Registrant (include ZIP Code):

Lanxess Corporation
 111 RIDC Park West Drive
 Pittsburgh, PA 15275-1112

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Antimicrobials Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA section 3(c)(7)(A). You must comply with the following conditions:

1. Submit and/or cite all data required for registration/reregistration/registration review of your product under FIFRA when the Agency requires all registrants of similar products to submit such data.

Signature of Approving Official:

Julie Chao, Product Manager 33
 Regulatory Management Branch 1, Antimicrobials Division (7510P)

Date:

10/5/15

2. You are required to comply with the data requirements described in the DCI identified below:
 - a. Bronopol GDCI-216400-1336

You must comply with all of the data requirements within the established deadlines. If you have questions about the Generic DCI listed above, you may contact the Reevaluation Team Leader (Team 36): <http://www2.epa.gov/pesticide-contacts/contacts-office-pesticide-programs-antimicrobial-division>

3. The data requirements for storage stability and corrosion characteristics (Guidelines 830.6317 and 830.6320) are not satisfied. A one year study is required to satisfy these data requirements. You have 18 months from the date of registration to provide these data.
4. Make the following label changes before you release the product for shipment:
 - Revise the EPA Registration Number to read, "EPA Reg. No. 39967-130."
5. Submit one copy of the final printed label for the record before you release the product for shipment.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

If you fail to satisfy these data requirements, EPA will consider appropriate regulatory action including, among other things, cancellation under FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions. A stamped copy of the label is enclosed for your records. Please also note that the record for this product currently contains the following CSFs:

- Basic CSF dated September 25, 2015

If you have any questions, please contact Zebora Johnson by phone at (703) 308-7080, or via email at johnson.zebora@epa.gov.

Sincerely,



Julie Chao, Product Manager 33
Regulatory Management Branch 1

Enclosure

Preventol® P 30 S

FOR THE PRESERVATION OF WATER-BASED PRINTING INKS, FOUNTAIN SOLUTIONS, METAL WORKING FLUIDS*, ABSORBENT CLAYS, PAINTS AND OTHER EMULSION SYSTEMS, CHEMICAL TOILET DEODORANTS*, DISINFECTANTS, CONSUMER, HOUSEHOLD AND INSTITUTIONAL PRODUCTS, ADHESIVES, STARCH, PIGMENT AND MINERAL SLURRIES, CONCRETE ADMIXTURES, RAW MATERIALS, SURFACTANTS, WATER BASED AGRICULTURAL PESTICIDE CONCENTRATES, PAPER MILLS – BULK PAPER, PAPER MILL PROCESS WATER, INDUSTRIAL COOLING WATER*, WATER FLOOD INJECTION WATERS, FRACKING FLUIDS, DRILLING AND WORKOVER FLUIDS, GAS STORAGE WELLS (*Not for use in the state of California)

ACTIVE INGREDIENT: 2-bromo-2-nitropropane-1,3-diol ----- 30%
INERT INGREDIENTS ----- 70%
TOTAL ----- 100.0%

KEEP OUT OF REACH OF CHILDREN DANGER

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER! Causes irreversible eye damage. May be fatal if swallowed or inhaled. Do not get in eyes or on clothing. Do not breathe vapor or spray mist. Wear protector eyewear such as goggles or face shield. Wash thoroughly with soap and water after handling and before eating, drinking and chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse. Wear a respirator with an organic-vapor removing cartridge with a filter approved for pesticides (MSHA/NIOSH approval number prefix TC-23C), or a canister approved for pesticides (MSHA/NIOSH approval number prefix TC-14G), or a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with any N, R, P or HE pre-filter.

FIRST AID

IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything to an unconscious person.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for treatment advice.

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a poison control center or doctor for treatment advice.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

Have the product container or label with you when calling a Poison Control Center or doctor for treatment advice.

The LANXESS Pittsburgh Emergency Response Telephone Number is 800-410-3063

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to the discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste.

IN CASE OF EMERGENCY, CALL: CHEMTREC 800-424-9300

EPA REGISTRATION NO: 39967-XX

EPA ESTABLISHMENT NO:

LANXESS

LANXESS Corporation

111 RIDC Park West Drive • Pittsburgh, PA 15275-1112

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Detailed directions for use can be found in the Preventol® P 30 S Product Information Sheet. Obtain and read this information before undertaking the use of Preventol® P 30 S in order to avoid processing mistakes.

PERSONAL PROTECTIVE EQUIPMENT

Applicators and other handlers must wear: Coveralls over long sleeved shirt and long pants, socks and chemical resistant footwear, goggles, face shield and chemical resistant gloves such as or made of any water-proof material. Wear a respirator with an organic-vapor removing cartridge with a filter approved for pesticides (MSHA/NIOSH approval number prefix TC-23C), or a canister approved for pesticides (MSHA/NIOSH approval number prefix TC-14G), or a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with any N, R, P or HE pre-filter. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions exist for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

USER SAFETY RECOMMENDATIONS

Users should wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet. Users should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users should remove personal protective equipment immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing.

PHYSICAL AND CHEMICAL HAZARDS

Avoid contact with metal equipment such as scoops, mills and sieves.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

PESTICIDE STORAGE: Product should be stored in an area that is not subject to extreme temperatures. Store in a cool, dry place and in such a manner as to prevent cross contamination with other pesticides, fertilizers, food, and feed.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the hazardous waste representative at the nearest EPA Regional office for guidance.

CONTAINER HANDLING: Nonrefillable container. Do not reuse or refill this container. Offer for recycling if available or reconditioning if appropriate. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in sanitary landfill, or incineration, or if allowed by state and local authorities, by burning. If burned, stay out of smoke.

Handle and open container in a manner as to prevent spillage. If the container is leaking, invert to prevent leakage. If the container is leaking material for any reason or cause, carefully dam up spilled material to prevent runoff. Refer to Precautionary Statements on label for hazards associated with the handling of this material. Do not walk through spilled material. Absorb spilled material with absorbing type compounds and dispose of as directed above.

® Preventol is a registered trademark of LANXESS Corporation

INTERNATIONAL 703-527-3887

Net Contents:

Lot/BATCH No.:

ACCEPTED

Oct 05, 2015

Under the Federal Insecticide, Fungicide and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 39967-130

LABEL TEXT DATE: 4/27/15

LANXESS

Energizing Chemistry

Product Information

PREVENTOL[®] P 30 S S

EPA Registration Number 39967-XX
CAS Number: 52-51-7

PREVENTOL® P 30 S

PREVENTOL® P 30 S S IS EFFECTIVE AGAINST THE GROWTH OF SLIME-FORMING, SPOILAGE, ODOR CAUSING AND CORROSION INDUCING BACTERIA AND ALGAE IN WATER-BASED PRINTING INKS,

FOUNTAIN SOLUTIONS, METAL WORKING FLUIDS*, ABSORBENT CLAYS, PAINTS AND OTHER EMULSION SYSTEMS, CHEMICAL TOILET DEODORANTS*, DISINFECTANTS, CONSUMER, HOUSEHOLD AND INSTITUTIONAL PRODUCTS, ADHESIVES, STARCH, PIGMENT AND MINERAL SLURRIES, CONCRETE ADMIXTURES, RAW MATERIALS, SURFACTANTS, WATER BASED AGRICULTURAL PESTICIDE CONCENTRATES, PAPER MILLS – BULK PAPER, PAPER MILL PROCESS WATER, INDUSTRIAL COOLING WATER*, WATER FLOOD INJECTION WATERS, FRACKING FLUIDS, DRILLING AND WORKOVER FLUIDS, , GAS STORAGE WELLS (*Not for use in the state of California

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

The following guidance is given as an approximation for each use pattern, but field-testing is recommended to achieve optimum effectiveness.

GENERAL USE DIRECTIONS

To control the growth of slime-forming, spoilage, odor-causing and corrosion inducing bacteria and algae in industrial applications, PREVENTOL® P 30 S S can be dosed directly, or by preparing a stock

solution immediately prior to application, either by open pouring (not cooling water treatment) or by metered pump. For process application treatments PREVENTOL® P 30 S S may be slug dosed initially

when the system is not noticeably fouled and reduced to a maintenance dose once microbial control is evident. For some applications treatment may be by slug dose or by maintenance dose only. More frequent and higher dosing should be used when contamination is heavy. The recommended dosing regimes (slug/maintenance dose) and the dose rates are as indicated in the individual use area instructions.

For preservation during the manufacture, distribution, storage and use of industrial, consumer, household and institutional products PREVENTOL® P 30 S S is best added at any liquid phase as late

as possible during the manufacturing process. It may be added by pre-dissolving in any water to be incorporated into the formulation. Add after any heating stage, or when the product has been cooled below 40°C. Ensure good mixing and even distribution throughout the product.

Do not apply this product in anyway that will contact workers or other persons.

WATER-BASED PRINTING INKS AND FOUNTAIN SOLUTIONS

During the use of fountain solutions, shock dose PREVENTOL® P 30 S S at 166.7 to 333.3 ppm (1.34

to 2.67 lb./1000 gallons) depending on the contamination. Apply once weekly in the fount reservoir as a normal routine or more frequently, if required.

For In-Can preservation dose PREVENTOL® P 30 S S at 333 to 1667 ppm based on the final formulation volume (2.67 to 13.4 lb./1000 gallons).

METAL WORKING FLUIDS(NOT FOR USE IN THE STATE OF CALIFORNIA)

For use in soluble oils, semi-synthetic and synthetic fluids. Add directly to the sump (with agitation) and allow to circulate for about one hour before shutdown. PREVENTOL® P 30 S S may be

incorporated in the metalworking fluid concentrate by the manufacturer who should ensure that any incompatibility will not affect the efficacy.

In diluted fluids add 333 to 3,333 ppm of PREVENTOL® P 30 S S (3.3 lb. of PREVENTOL® P 30 S S in 1000

lbs. will give a dose level of 1000 ppm)

ABSORBENT CLAYS, CORN COBS, AND GROUND WOOD

For preservation, impregnate absorbent clays, corn cobs, or ground wood with PREVENTOL® P 30 S S

to inhibit the growth of odor causing bacteria by spraying or pouring solution of 83 to 667 ppm (0.10 to 0.810 oz av. per 100 pounds of absorbent material).

PAINTS AND OTHER EMULSION SYSTEMS

For the preservation of acrylic, styrene-acrylic, polyvinyl acetate and other latex emulsions, latex emulsion based paints, photographic emulsions, silicone and other antifoam emulsion systems. Add PREVENTOL® P 30 S S at 333 to 1667 ppm based upon the final formulation volume (2.67 to 13.35 lb./1000 gallons).

CHEMICAL TOILET DEODORANTS

To inhibit the growth of odor-causing bacteria in toilets, chemical deodorant concentrates should incorporate PREVENTOL® P 30 S S at levels of 3.3 to 93% depending upon the desired concentration

level. To effectively control odor in a portable toilet, a level of 333 to 1667 ppm of PREVENTOL® P 30 is recommended.

GENERAL PRESERVATION

For the preservation of industrial products such as adhesives, starch, pigments, mineral slurries, paint and emulsion systems such as acrylic, styrene acrylic, and polyvinyl acetate, other latex emulsions, latex emulsion based paints, photographic* emulsions, silicone and other antifoam emulsion systems. Consumer, household and institutional products such as dishwashing liquids, surface cleaners and polishes. Surfactants and raw materials for the manufacture of industrial and consumer products, also industrial water additive formulations for use in processes such as cooling water, process water, boiler water and waste water products.

For general preservation applications, PREVENTOL® P 30 S S should be dosed at 333 to 1667 ppm

based on the final formulation volume (2.67 lbs. to 13.35 lbs./1000 gallons). For difficult to preserve formulation such as adhesives and those containing naturally derived ingredients, doses up to 3,333 ppm (0.3 lb per 100 lb. total formulation weight) may be required.

CONCRETE ADMIXTURES

For the preservation of concrete admixtures based on polycarboxylates, lignosulphonates, naphthalene sulphonates, melamine sulphonates and other systems.

Add PREVENTOL® P 30 S S at 250 to 2500 ppm based upon the final formulation volume (2.1 to 21 lbs./1000 gallons).

WATER BASED AGRICULTURAL PESTICIDE CONCENTRATES

For preservation, PREVENTOL® P 30 S S should be dosed at 333 to 1667 ppm based on the final formulation volume (2.67 lbs. to 13.35 lbs./1000 gallons).

PAPER MILLS – BULK PAPER

Add PREVENTOL® P 30 S S directly into the hydropulper, machine chest or stock chest. Apply once

weekly to once daily at 167 to 667 ppm (0.4 – 1.5 lbs. per ton).

PAPER MILL PROCESS WATER

Apply at a convenient point early in the process system (machine chest, constant head box or backwater loop system). Dose PREVENTOL® P 30 S S once to three times daily at 3.3 to 83 ppm in the

process water. This equates to 0.07 to 1.66 lbs. per ton of finished paper or paperboard.

PREVENTOL® P 30 S S

39967-64

Page 4

INDUSTRIAL COOLING WATER(Not for use in the State of California)

For use in cooling towers, evaporative condensers, open and closed loop cooling and stored (nonpotable)

water, industrial and/or commercial air washers, air conditioning and humidifying systems.

PREVENTOL® P 30 S S will reduce the biofouling of pipe work, heat exchangers, and condenser tubes

and minimize microbial-induced corrosion. Apply PREVENTOL® P 30 S S once weekly to once monthly

to the sump or tank where turbulence and flow will ensure quick dissolution. Do not apply by open pouring of liquid to cooling water systems; a metering pump delivery system is required for this use and application method.

Shock dose PREVENTOL® P 30 S S at 167 to 333 ppm (1.4 to 2.8 lbs./1000 gallons). Subsequent dosing can be reduced to 83 ppm.

WATER FLOOD INJECTION WATER

Initial Treatment: When the system , add 83.3 to 333 ppm PREVENTOL® P 30 S S to the system (0.083 to 0.3333 gallons PREVENTOL® P 30 S S per 1000 gallons flood water) . Repeat until control

is achieved. Subsequent Dose: When microbial control is evident, add 83.3 to 333.3 ppm PREVENTOL® P 30 S S (0.083 to 0.3333 gallons per 1000 gallons flood water) to the system weekly,

or as needed to maintain.

FRAC FLUIDS

Add PREVENTOL® P 30 S S to the frac water storage tanks or directly into the well head injection pipeline as the water is being pumped down-hole.

Dose Range: Preventol P 30 S S should be added at a rate of 166.7-333.3 ppm (0.1667– .3333 gallons per 1000 gallons) depending on the degree of bacterial fouling in the source water.

DRILLING, COMPLETION AND WORKOVER FLUIDS

PREVENTOL® P 30 S S should be added to a drilling fluid system at a point of uniform mixing such as the circulating mud tank. Initial treatment: Add 166.7-333 ppm PREVENTOL® P 30 S S (0.525 – 1.049. gallons PREVENTOL® P 30 S S per 100 barrels of fluid) to a freshly prepared fluid depending on the severity of contamination. Maintenance dosage: Maintain a concentration of 166.7 to 333.3 ppm of PREVENTOL® P 30 S S by adding 0.525 to 1.049 gallons of PREVENTOL® P 30 S S per 100 barrels of additional fluid, or as needed, depending on the severity of the contamination.

GAS STORAGE WELLS AND SYSTEMS

Individual injection wells should be treated with a sufficient quantity of PREVENTOL® P 30 S S to produce a concentration of 83.3 to 666.6 ppm PREVENTOL® P 30 S S when diluted by the water present in the formation. Injection should take place before gas is injected (during the summer). Injections should be repeated yearly, or as needed to maintain control. Individual

PREVENTOL® P 30 S

39967-64

Page 4

drips should be treated with a sufficient quantity of PREVENTOL® P 30 S S to produce a concentration of 83.3 to 666.6 ppm PREVENTOL® P 30 S S when diluted by the water present in the drip. Injections should be repeated yearly, or as needed to maintain control.

REMARKS

If you need assistance or information, please call your nearest LANXESS representative, or our Pittsburgh office at 800-LANXESS.

**IN CASE OF EMERGENCY, CALL: CHEMTREC 1-800-424-9300
INTERNATIONAL (703)-527-3887**

HAVE THE PRODUCT CONTAINER OF LABEL WITH YOU WHEN CALLING A POISON CONTROL CENTER OR DOCTOR OR GOING FOR TREATMENT.

LANXESS Corporation
111 RIDC Park West Drive
Pittsburgh, PA 15275
412-809-1000

The conditions of your use and application of our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. This application-specific analysis at least must include testing to determine suitability from a technical as well as health, safety and environmental standpoint. Such testing has not necessarily been done by LANXESS Corporation. All information is given without warranty or guarantee. It is expressly understood and agreed that the customer assumes and hereby expressly releases LANXESS from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance and information. Any statement or recommendation not contained herein is unauthorized and shall not bind LANXESS. Nothing herein shall be construed as a recommendation to use any product in conflict with patents covering any material or its use. No license is implied or in fact granted under the claims of any patent.

2/15